



# STREAMCASTER® 4400 XTREME

AS TOUGH AS THE MISSION

The SC4400X delivers the proven performance of the StreamCaster 4400 MANET radio in an ultra-ruggedized, corrosion-resistant form factor. With up to 20 Watts of output power and 100 Mbps data throughput and powered by Silvus' battle-proven MN-MIMO waveform – the SC4400X enables mission-critical connectivity in the world's harshest environments.

## Key Features

**Ultra-Rugged Enclosure:** Constructed from sea-grade aluminum with MIL-A-8625-F Type III hard anodizing and locking marine grade I/O connector for superior corrosion resistance

**Enhanced Thermal Protection:** Optimized enclosure with enhanced thermal characteristics improve passive cooling and thermal performance during sustained high-power operations

**Flexible Power Input:** 9-50 VDC input range supports diverse deployment platforms

**Visual Status Feedback:** Integrated LED provides at-a-glance operational status

**Mechanical Compatibility:** Matches SC4400 mounting pattern for seamless integration with existing systems and accessories

# STREAMCASTER 4400 XTREME

Thermally Optimized Design | Corrosion-Resistant Connectors | Powerful Performance

Type 3, Hard Anodizing for Maximum Toughness



Corrosion-Resistant Antenna Ports

Single Locking Marine Grade Connector

LED Status Light

## SPECIFICATIONS

### GENERAL

MODEL NUMBER	NATIVE TX POWER User Adjustable	EFFECTIVE TX POWER w/ Beamforming
SC4480X	1mW – 8W	Up to 32W
SC44K0X	1mW – 20W	Up to 80W
WAVEFORM	Mobile Networked MIMO (MN-MIMO)	
ENCRYPTION	DES56 (Standard) AES256 (Optional) FIPS 140-3 Level 2	
DATA RATE	Up to 100Mbps (Adaptive)	
MIMO TECHNIQUES	Spatial Multiplexing, Space-Time Coding, TX/RX Eigen Beamforming	
PUSH-TO-TALK VOICE	G.711/G.722/Opus Codec	
LATENCY	7ms average (20MHz BW)	
SENSITIVITY	-102dBm @ 5MHz BW -108dBm @ 1.25MHz BW (optional)	
FREQUENCY BANDS	Bands from 300MHz to 6GHz available	
CHANNEL BANDWIDTH (MHZ)	20/10/5 (2.5/1.25 Optional)	
SCALABILITY	550+ Nodes	

### SPECTRUM DOMINANCE 2.0

LPI/LPD, ANTI-JAM & ADVANCED THREAT PROTECTION CAPABILITIES

#### AVAILABLE FEATURES

MANET Spectrum Analyzer (MAN-SA)	
MANET Power Control (MAN-PC)*	Wake on Wireless
MANET Interference Cancellation (MAN-IC)*	
MANET Interference Avoidance (MAN-IA)	Dual Frequency Link
MANET Protected Waveform (MAN-PW)*	

\*ITAR Controlled

### FREQUENCY BAND OPTIONS

(all bands listed in MHz; dual band configurations available)

BAND	CODE	RANGE	BAND	CODE	RANGE
UHF	034	300 - 380	BROADCAST	206	2025 - 2110
	042	400 - 450	S	225	2200 - 2300
	068	663 - 698		235	2200 - 2500
900 MHz ISM	091	902 - 928	2.4 GHz ISM	245	2400 - 2500
L	137	1350 - 1390	C	467	4400 - 4940
	139	1350 - 1440		470	4400 - 5000
	147	1452 - 1492		485	4700 - 5000
	150	1492 - 1525	PUBLIC SAFETY	512	4940 - 5300
	179	1790 - 1805	5 GHz ISM	520	5150 - 5250
	182	1790 - 1850		580	5725 - 5875

Note: If band of interest is not listed, please contact a sales representative

### MECHANICAL

OPERATING TEMPERATURE	-40° to +85° C
IP RATING	IP67
DIMENSIONS*	139.7 mm x 135.35 mm x 59.69 mm
WEIGHT	1285 grams
MATERIAL	Sea Grade Al 5083; Type 3 hard anodizing

\* Without RF Connectors

### POWER

INPUT VOLTAGE	9-50 VDC
POWER CONSUMPTION	8W-25W @ 1W TX Power 8W-45W @ 8W TX Power 8W-105W @ 20W TX Power

### INTERFACES

RF	4x TNC(f) N(f) Optional
PRIMARY	Marine-grade 37-pin Circular Connector: 1x Ethernet; 1x RS232 1x USB2.0 Host; 1x USB2.0 OTG Push-to-Talk BDA Control; DC Input
STATUS INDICATOR	Bi-Color LED



Learn More

[www.silvustechologies.com](http://www.silvustechologies.com)

The following notice applies to the sale, lease, or offer of this device other than for use by the United States Government or for export. This device has not been authorized as required by the rules of the Federal Communications Commission. This device is not, and may not be, offered for sale or lease, or sold or leased, until authorization is obtained. Please contact Silvus for questions about the FCC approval status or requirements that pertain to this device including whether an FCC approved version is available. Exported devices are subject to the laws of the countries into which they are exported.