

STREAMCASTER® NEXUS



NEXT GEN TACTICAL NETWORKING FOR THE DISMOUNTED OPERATOR

Seamlessly pairing the ultra-slim SM5200 MANET radio with Samsung's mission-ready EUD, StreamCaster NEXUS delivers mission-critical connectivity and real-time situational awareness. Custom designed Juggernaut chest-mount features streamlined, snag-free cable routing that minimizes weight and maximizes operator freedom.



STREAMCASTER NEXUS



OPERATOR CENTRIC LOW PROFILE DESIGN

Compact, modular design reduces operator load-out, maximizing mission-focused mobility

- Ruggedized for the mission Juggernaut Armor δ VELOX chest mount configurations
- Ultra-slim & lightweight streamlined & snag-free cable management
- Low profile design SM5200 MANET radio virtually disappears into vest



ADVANCED NETWORKING AT MISSION SPEED

StreamCaster SM5200 MANET radio delivers assured voice, high-fidelity video and IP data communications

- Up to 2W Native, 4W Effective TX power
- Up to 100 Mbps data rate
- MN-MIMO waveform 550+ node scalability
- Dual PTT with independent L/R audio
- Dedicated RoIP interface



CENTRAL HUB FOR THE CONNECTED OPERATOR

Samsung S23/S23TE provides real-time situational awareness, mission planning & radio configuration

- ► ATAK access geospatial, sensor & cursor on target intelligence
- ► StreamScape ATAK plug-in SM5200 & configurable PTT settings
- Multiple I/O connectors Ethernet, USB, RS232
- Nett Warrior unified radio/EUD power distribution




ACHIEVE SPECTRUM DOMINANCE

Access ever-expanding suite of LPI/LPD, Anti-Jam and Advanced Threat Protection capabilities


- Secure & protected comms without sacrificing performance
- Designed to thrive in EW contested environments
- Achieve mission objectives even under electronic attack

TACTICAL NETWORKING SYSTEM



STREAMCASTER NEXUSISPECS

TRANSMIT POWER NATIVE TX POWER EFFECTIVE TX POWER User Adjustable w/Beamforming ImW – 2W Up to 4W WAVEFORM Mobile Networked MIMO (MN-MIMO
WAVEFORM Mobile Networked MIMO (MN-MIMO
ENCRYPTION AES256; FIPS 140-3 DATA RATE Up to 100 Mbps (Adaptive
FREQ. BANDS (MHz) L (1350-1440); S (220-2500); C (4400-5000 L65 (1350-1440) + (2200-2500 S6C (2200-2500) + (4400-5000
CHANNEL BANDWIDTH (MHz) 20/10/5 (2.5/1.25 Optional
SCALABILITY 550+ Node:
SPECTRUM DOMINANCE 2.0 MANET Spectrum Analyzer (MAN-SA LPI/LPD, ANTI-JAM 6 MANET Power Control (MAN-PC) ADVANCED THREAT MANET Interference Avoidance (MAN-IA PROTECTION MANET Interference Cancellation (MAN-IC) CAPABILITIES MANET Protected Waveform (MAN-PW) *ITAR-Controlled
POWER INPUT USP-PD (9V@3A) or 9-32 VD0
POWER CONSUMPTION 4-13W (a) 2W TX Power (SM5200
ENVIRONMENTAL IP68
DIMENSIONS 103.5 x 68.0 x 13.3 mm (Radio Only 178 x 124 x 40 mm (Total System
WEIGHT 182 grams (Radio Only




Streamlined Cable Management Snag-Free Design



Removable SM5200 MANET radio for Standalone Operation

AGILE TECH FOR THE WAY YOU OPERATE | TACTICAL GEAR OPTIONS





Silvustechnologies.com TECHNOLOGIES E: info@silvustechnologies.com

The following notice applies to the sale, lease, or offer of this device other than for use by the United States Government or for export: This device has not been authorized as required by the rules of the Federal Communications Commission. This device is not, and may not be, offered for sale or lease, or sold or leased, until authorization is obtained. Please contact Silvus for questions about the FCC approval status or requirements that pertain to this device including whether an FCC α approved version is available. Exported devices are subject to the laws of the countries into which they are exported.